UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/575,516	04/13/2006	Peter Berenbrink	2003P12192WOUS	3915
22116 7590 04/14/2008 SIEMENS CORPORATION INTELLECTUAL PROPERTY DEPARTMENT 170 WOOD AVENUE SOUTH ISELIN, NJ 08830			EXAMINER	
			KIM, TAE JUN	
			ART UNIT	PAPER NUMBER
			3746	
			MAIL DATE	DELIVERY MODE
			04/14/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/575,516	BERENBRINK ET AL.
Office Action Summary	Examiner	Art Unit
	Ted Kim	3746
The MAILING DATE of this communication ap Period for Reply	ppears on the cover sheet with the o	correspondence address
A SHORTENED STATUTORY PERIOD FOR REP WHICHEVER IS LONGER, FROM THE MAILING I - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication.  If NO period for reply is specified above, the maximum statutory perior Failure to reply within the set or extended period for reply will, by statu. Any reply received by the Office later than three months after the mail earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION 1.136(a). In no event, however, may a reply be tind will apply and will expire SIX (6) MONTHS from the cause the application to become ABANDONE	N. mely filed the mailing date of this communication. ED (35 U.S.C. § 133).
Status		
Responsive to communication(s) filed on 16.  2a) This action is <b>FINAL</b> . 2b) Th  3) Since this application is in condition for allow closed in accordance with the practice under	nis action is non-final. vance except for formal matters, pro	
Disposition of Claims		
4)  Claim(s) 8-18 is/are pending in the applicatio 4a) Of the above claim(s) is/are withdr 5)  Claim(s) is/are allowed. 6)  Claim(s) 8-17 is/are rejected. 7)  Claim(s) 18 is/are objected to. 8)  Claim(s) are subject to restriction and/ Application Papers  9)  The specification is objected to by the Examination The drawing(s) filed an is/are; s\	rawn from consideration.  /or election requirement.  ner.	Eva minor
10) The drawing(s) filed on is/are: a) according a depth of the	e drawing(s) be held in abeyance. Se ection is required if the drawing(s) is ob	e 37 CFR 1.85(a). ejected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority application from the International Bure * See the attached detailed Office action for a list	nts have been received. nts have been received in Applicat iority documents have been receive au (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date	4)  Interview Summary Paper No(s)/Mail D 5)  Notice of Informal F 6)  Other:	ate

Art Unit: 3746

#### **DETAILED ACTION**

## Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 8, 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Braun et al (2001/0023578) in view of EP 1331448 and optionally in view of Iizuka et al (4,766,721). Braun et al teach a method for compensating variations in a fuel composition in a gas turbine system having a plurality of burner stages 5, 1 operated in parallel, comprising: adjusting a fuel supply to the burner stages 5, 1 in response to the variations in the fuel composition; splitting the fuel supply via valves 19a, 19b between the burner stages; wherein the gas turbine system comprises a pilot burner 11 stage and a main burner stage 5 and the fuel supply split between the pilot burner stage and the main burner; wherein a plurality of fuel control valves 19a, 19b are provided to the burner stages, wherein a regulator 27 is allocated to the fuel control valves. Braun et al do not teach the fuel supply split between the burner stages at a constant target value during the adjustment of the fuel supply. EP '448 teaches maintaining the desired fuel flow split (page 5, paragraph 1, see Fig. 3) between the primary and secondary burner stages in the combustor of a gas turbine. EP '448 teaches using this type of fuel trimming allows for

Application/Control Number: 10/575,516

Page 3

Art Unit: 3746

lower NOx emissions as it limits the maximum fluctuation of fuel flow and (see e.g. 2, lines 29-36) and a constant fuel/air ratio for the combustion process (page 4, lines 47-52). It would have been obvious to one of ordinary skill in the art to employ a constant split between the burner stages, as taught by EP '448 et al, in order to provide a constant fuel/air ratio in each combustor stage and/or or to limit the fluctuations of the fuel flow. Note that as the same fuel source 33, 37, BH is used for both burner stages in Braun et al and any fluctuation in the fuel composition will directly affect the fuel calorific value. Hence, for at least small changes in the fuel composition/calorific value, the split between the burners should remain at a constant split, since each burner would be equally affected by the change in the fuel calorific value, and stability is promoted by a maintaining a constant fuel/air ratio for each stage, as set forth in EP '448. It would have been obvious to one of ordinary skill in the art to maintain the split of fuel constant in response to variations during the adjustment of the fuel supply, as a conventional technique in splitting the fuel and in keeping with the desire to keep the fuel/air ratio in each burner constant. The above prior art inherently are pilot and main burners, as would be known in the art. In order to obviate any doubt, Iizuka et al teach the central diffusion stage is the pilot stage and radially outer stages are premixed main stages (see col. 1, lines 10+ and col. 9, lines 8-22 and col. 4, lines 7+). It would have been obvious to one of ordinary skill in the art to make the central burner the pilot stage the outer stages the main premixed stages, as taught by Iizuka et al, as the conventional practice for these configurations of burners.

Application/Control Number: 10/575,516

Page 4

Art Unit: 3746

3. Claims 8, 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwata et al (5,327,718) in view of Beebe et al (5,319,931). Iwata et al teach a method for compensating variations in a fuel composition in a gas turbine system having a plurality of burner stages (from fuel nozzles 9 and 19) operated in parallel, comprising: adjusting a fuel supply F to the burner stages in response to the variations in the fuel composition 30; splitting the fuel supply between the burner stages via e.g. valve 8a, 8b; wherein the gas turbine system comprises a pilot burner 9 stage and a main burner stage 19 (see col. 8, lines 18-27, which teach the pilot diffusion burner 9 is mainly effected at startup, while the main premixing burner stage 19 is mainly effected above a certain load, and thus the pilot burner stage is low during the main load operation). Beebe et al teach (col. 5, lines 29-37) that it is old and well known in the gas turbine art to maintain the split between the primary and secondary burner stages in the combustor. Beebe et al teach using this type of fuel trimming allows for lower NOx emissions as it limits the maximum fluctuation of fuel flow (see e.g. col. 6, lines 13-23) and a constant fuel/air ratio for the combustion process (col. 5, lines 9-13). It would have been obvious to one of ordinary skill in the art to employ a constant split between the burner stages, as taught by Beebe et al, in order to provide a constant fuel/air ratio in each combustor stage or to limit the fluctuations of the fuel flow. Note that as the same fuel source FP is used for both burner stages in Braun et al and any fluctuation in the fuel composition will directly affect the fuel calorific value. Hence, for at least small changes in the fuel composition/calorific value, the split between the burners should remain at a constant split, since each burner

would be equally affected by the change in the fuel calorific value, and stability is promoted by a maintaining a constant fuel/air ratio for each stage, as set forth in Beebe et al.

4. Claims 10-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Iwata et al (5,327,718) in view of Beebe et al (5,319,931) as applied above, and further in view of Vandervort (6,082,092). The above prior art teach an analyzer calculating the calorific value of the fuel (see Iwata et al 29), an updating unit 30 or 32 adjusting the regulator 29 and control valves 8a, 8b based on the calorific value. The above prior art do not teach using a current Wobbe analysis and using the Wobbe index in the updater unit. Vandervort teaches that the Wobbe number uses the calorific value divided by the square root of the absolute temperature \* the specific gravity, see the equation on col. 2. Thus the Wobbe Number is directly proportional to the calorific value and is a better index of determining compatibility of gas turbine fuel systems with different fuels than the calorific value alone (see e.g. col. 1, lines 62+). Vandervort further teaches using a measured Wobbe number with a desired Wobbe number allows reduction of combustor dynamics and damage. The calculated Wobbe number 40 is compared to an expected Wobbe number 44 and the results used in an updating unit 42. It would have been obvious to one of ordinary skill in the art to employ the current Wobbe analysis and using the Wobbe index in the updater unit, as taught by Vandervort, to better determining compatibility of gas turbine fuel systems with different fuels than the calorific value alone and/or to reduce combustor dynamics and damage. As for the computing unit,

Art Unit: 3746

regulator, and updating unit being separate or integrated, these options are both well within the ordinary skill in the control art. These were illustrated as separate control blocks and making them integral or separate is an obvious matter of using the conventional ways of implementing them, for either a modular approach or an integrated approach with fewer units.

## Allowable Subject Matter

5. Claim 18 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

#### Response to Arguments

- 6. Applicant's arguments filed 01/16/2008 have been fully considered and are persuasive with regard to the Urishidani et al reference but they are not persuasive with respect to the Braun and EP '448.
- 7. Applicant's argues that EP '448 teaches "maintaining a desired fuel flow split without regard to whether the split is kept at a constant value or varied over time." In rebuttal, EP '448 teaches "maintaining a desired fuel flow split." The desired fuel flow split is maintained, implicitly requires keeping a constant fuel flow split. Furthermore, there is nothing in the claims to indicate how long the split is maintained at a constant value, hence, applicant is arguing a period of time which is simply not in the claims.
- 8. Applicant's argues that proposed combination of references is a piecemeal combination based on hindsight. In response to applicant's argument that the examiner's

Page 7

conclusion of obviousness is based upon improper hindsight reasoning, it must be recognized that any judgment on obviousness is in a sense necessarily a reconstruction based upon hindsight reasoning. But so long as it takes into account only knowledge which was within the level of ordinary skill at the time the claimed invention was made, and does not include knowledge gleaned only from the applicant's disclosure, such a reconstruction is proper. See *In re McLaughlin*, 443 F.2d 1392, 170 USPQ 209 (CCPA 1971). EP '448 teaches maintaining the desired fuel flow split (page 5, paragraph 1, see Fig. 3) between the primary and secondary burner stages in the combustor of a gas turbine. EP '448 teaches using this type of fuel trimming allows for lower NOx emissions as it limits the maximum fluctuation of fuel flow and (see e.g. 2, lines 29-36) and a constant fuel/air ratio for the combustion process (page 4, lines 47-52). It would have been obvious to one of ordinary skill in the art to employ a constant split between the burner stages, as taught by EP '448, in order to provide a constant fuel/air ratio in each combustor stage and/or or to limit the fluctuations of the fuel flow. Note that as the same fuel source 33, 37, BH is used for both burner stages in Braun et al and any fluctuation in the fuel composition will directly affect the fuel calorific value. Hence, for at least small changes in the fuel composition/calorific value, the split between the burners should remain at a constant split, since each burner would be equally affected by the change in the fuel calorific value, and stability is promoted by a maintaining a constant fuel/air ratio for each stage, as set forth in EP '448. It would have been obvious to one of ordinary skill in the art to maintain the split of fuel constant in response to

Art Unit: 3746

variations during the adjustment of the fuel supply, as a conventional technique in splitting the fuel and in keeping with the desire to keep the fuel/air ratio in each burner constant.

9. Due to the application of new art above, specifically the Iwata et al combination, this action is made non-Final.

Art Unit: 3746

# **Contact Information**

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Ted Kim whose telephone number is 571-272-4829. The Examiner can be reached on regular business hours before 5:00 pm, Monday to Thursday and every other Friday.

The fax number for the organization where this application is assigned is 571-273-8300.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Devon Kramer, can be reached at 571-272-7118. Alternate inquiries to Technology Center 3700 can be made via 571-272-3700.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). General inquiries can also be directed to the Patents Assistance Center whose telephone number is 800-786-9199. Furthermore, a variety of online resources are available at <a href="http://www.uspto.gov/main/patents.htm">http://www.uspto.gov/main/patents.htm</a>

/Ted Kim/	Telephone 571-272-4829
Primary Examiner	Fax (Regular) 571-273-8300
April 14, 2008	Fax (After Final) 571-273-8300
Technology Center 3700	Telephone 571-272-3700